AccelTex SOLUTIONS

802.3AF AND 802.3AT 30 WATT POE INJECTOR ATS-30W-POE-INJ

MECHANICAL SPECIFICATIONS

Dimensions: 6.89" L x 3.62" W x 1.26" H (175 mm L x 92 mm W x 32 mm H) Connector: 2 RJ-45 Jacks LAN Port: 10/1000

4

ELECTRICAL SPECIFICATIONS

Input Voltage: 100/240 VAC 50/60HZ 0.3A Output Voltage: 52 VDC 0.5A Max Load: 30 Watts Comes with U.S. Line Cord Upstream port lightning protection

ENVIRONMENTAL SPECIFICATIONS

Installation Environment: Indoor Operating Temperature: 32 to 104°F (0 to 40°C) Storage Temperature: -40 to 158°F (-40 to 70°C) Operating Humidity: 10% to 90% RH (non-condensing)

LED INDICATORS

On: Power OK



The facts and figures herein are carefully compiled to the best of our knowledge and are intended for general informational purposes only. Responsibility for the use and application of AccelTex Solutions materials rests with the end user. All AccelTex Solutions products are sold pursuant to the AccelTex Solutions Terms and Conditions of Sale. © 2020 AccelTex Solutions. All Rights Reserved. AccelTex, AccelTex Solutions, the AccelTex Solutions Logo and other marks are trademarks or registered trademarks of AccelTex Solutions. Other products or service names may be the property of third parties.

1.888.406.8906 SALES@ACCELTEX.COM